







DESCRIPTION

- ◆ CCT Selectable 4000K,5000K and Wattage Selectable.
- ◆ 0-10V dimming capability is standard.
- ◆ Painted steel housing and PC (polycarbonate) matte lenses are standard.
- ◆ Chain-mount kits (includes v-hooks and 1/8" thick, 1-meter long chain) are standard.
- ◆ Options include wire-guard kits, pendant mount kits, surface mount kits, PIR Sensor and DC microwave sensor
- ◆ cULus listed for damp locations in ambient temperatures from -30°C to 50°C.
- ◆ 5-year warranty.

LED LINEAR HIGHBAY LIGHT



ACCESSORIES


| | | |
|---|--|---|
|  Pendant Mount |  Surface Mount |  Sensor |
|  Chain Mount |  Wire Guard |  Lifting Rope |
|  Emergency driver | | |




| Watt | Voltage | Lumens | Efficacy | Net Weight | Wattage Selectable | CCT Selectable | PF | CRI | Beam Angle |
|------|----------------------------|----------------|--------------|------------|--------------------|----------------|------|-----|------------|
| 85W | 120-277 Vac 220-240 Vac | 11475-11900 lm | 135-140 lm/w | 2.4 KG | Wattage Selectable | 4000K 5000K | ≥0.9 | >80 | 90° |
| 110W | | 14850-15400 lm | 135-140 lm/w | 2.4 KG | | | | | |
| 130W | | 17550-18200 lm | 135-140 lm/w | 2.5 KG | | | | | |
| 165W | | 22275-23100 lm | 135-140 lm/w | 2.6 KG | | | | | |
| 220W | | 29700-30800 lm | 135-140 lm/w | 3.3 KG | | | | | |
| 255W | | 34425-35700 lm | 135-140 lm/w | 3.3 KG | | | | | |
| 300W | 40500-42000 lm | 135-140 lm/w | 3.4 KG | | | | | | |

DIMENSIONS


85W,110W




85W,110W,130W,165W



220W



255W,300W



INSTALLATION DIAGRAM

