




DESCRIPTION

- ◆ Module adjustable.
- ◆ CCT Selectable 4000K,5000K and Wattage Selectable.
- ◆ 0-10V dimming capability is standard.
- ◆ Painted steel housing and PC (polycarbonate) matte lenses are standard.
- ◆ Chain-mount kits (includes v-hooks and 1/8" thick, 1-meter long chain) are standard.
- ◆ Options include wire-guard kits, pendant mount kits, surface mount kits, PIR Sensor and DC microwave sensor.
- ◆ cULus listed for damp locations in ambient temperatures from -30°C to 50°C.
- ◆ Optics rotate up to 135°
- ◆ 5-year warranty.

LED LINEAR HIGHBAY LIGHT



ACCESSORIES


 Pendant Mount	 Surface Mount	 Sensor
 Chain Mount	 Wire Guard	 Lifting Rope
 Emergency driver		




Watt	Voltage	Lumens	Efficacy	Net Weight	Wattage Selectable	CCT Selectable	PF	CRI	Beam Angle
85W	120-277 Vac 220-240 Vac 120-347 Vac	11475-11900 lm	135-140 lm/w	2.4 KG	Wattage Selectable	4000K 5000K	≥0.9	>80	90°
110W		14850-15400 lm	135-140 lm/w	2.4 KG					
130W		17550-18200 lm	135-140 lm/w	2.5 KG					
165W		22275-23100 lm	135-140 lm/w	2.6 KG					
220W		29700-30800 lm	135-140 lm/w	3.4 KG					
255W		34425-35700 lm	135-140 lm/w	3.4 KG					
300W	120-277 Vac 220-240 Vac	40500-42000 lm	135-140 lm/w	3.5 KG					

DIMENSIONS


85W,110W



85W,110W,130W,165W



220W
255W
300W



INSTALLATION DIAGRAM

