DATE:	FIRMWARE:	ERP CODE:
VEDSION:	CATALOG#:	



RGBW 4 Channels Controller














FEATURES


DC4CH has 4 channel output, especially design for RGBW lights. Unlike other RGB controller produced a mixed white color, this controller is full RGBW with an independent white channel. Can stay alone or connecting with other Lumenativ devices.

- · 4 Channel output, light level dimming and RGBW colortuning
- Input polarity protection
- · Output overload protection
- · Fine Tuned RGBW color dimming


DIMENSION

Unit:inch/mm





WIRING



SPECIFICATIONS

Input Voltage: CV,DC 12-48V

Input Current: 8A

Output Voltage: DC 12-48V

Output Current: CC, 2Ax4CH Max

Bluetooth Transmit: 100ft Max

Radio Frequency: 2.4GHz ± 75MHz

Bluetooth Version: 4.2

Housing Material: UL 94V-0

Operating Temperature: -20°C to 50°C,

-4°F to 122°F

Storage Temperature: -30°C to 85°C,

-22°F to 185°F

IP Rating: IP20

Color: Black

Warranty: 5 years warranty

Comply to UL1376, RoHS

FCC ID: 2A26YLTKTVT2021

DID: D057145

DLC: NLTRC5KLOTN

MODEL	DESCRIPTION	
DC4CH	Bluetooth RGBW Controller	



MARKING



The Bluetooth word mark and logos are registered trademarks owned by Bluetooth STG, Inc. and any use of such marks by Litetrace is under license. Other trademarks and trade names are those of their respective owners.

APP DOWNLOAD







